

# BKG<sup>®</sup> Opti-Line™ Underwater Pelletizing System

**Throughput range up to 15,000 kg/hr (33,000 lb/hr)**

## Processes:

- Polymerization
- Masterbatch
- Compounding
- Recycling

## Materials:

- All materials which behave like thermo-plastic polymers (PE, PP, PS, ABS, SAN, PA, PET, PC, POM, TPE, TPU, EVA, APAO, PBT, PMMA, EPDM)



## Features:

- Modular design
- Completely skid-mounted
- Noise reduction of the pellet dryer  $\leq 80$  dB(A)
- Large dryer door for easy access
- Optional Fines Removal Sieve (curved screen) with filtration level 150 $\mu$ m
- Pre-dewatering
- Dryer available with inspection window and lights
- Cleaning system for the pellet dryer available
- Larger systems upon request

## Benefits:

- Premium options / features available
- Flexibility for material and / or color changes
- Easy and fast cleaning of the system components
- Easy operation, simple handling
- Process water tank can be heated via steam or other medium versus electrical heating
- Explosion protected design according to ATEX available

Model	Pellet Dryer	Capacity
Opti-Line™ 1	TVE 2004 SR	< 1,200 kg/hr (2,600 lb/hr)
Opti-Line™ 2	TVE 2004 SR	< 2,500 kg/hr (5,500 lb/hr)
Opti-Line™ 3	TVE 6002 SR	< 5,000 kg/hr (11,000 lb/hr)
Opti-Line™ 4	TVE 6002 SR	< 7,500 kg/hr (16,500 lb/hr)
Opti-Line™ 5	TVE 12000 SR	< 15,000 kg/hr (33,000 lb/hr)

**Nordson BKG GmbH**  
Hessenweg 3  
48157 Münster / Germany  
+49.251.26501.0 **Phone**

**USA**  
+1.828.326.9888 **Phone**

**China**  
+86.21.5785.091.8 **Phone**

www.nordsonpolymerprocessing.com | info@nordsonpolymerprocessing.com  
© 2015 Nordson BKG GmbH  
Printed in USA  
8/2016

